
TabSINT Protocol Development Workshop: Session 4



Tristan Ramey
Marc Shapiro

April 8, 2019

Agenda


- **Navigation Menu**
- **Dynamic Logic**

Videos of the tutorials from the first three workshops are available [here](#) as part of the TabSINT documentation

Navigation Menu

- Drop-down menu in top right
- Customizable (protocol_schema.json)
 - Array of objects
 - Three required fields
 - » text
 - » target
 - » returnHereAfterward

```
"protocolId": "session4_demo",
"title": "Protocol Development Workshop",
"subtitle": "Session 4",
"navMenu": [
  {
    "text": "navMenu Option",
    "target": {
      "reference": "option"
    },
    "returnHereAfterward": true
  }
],
```



Dynamic Logic

- **Custom expressions**
- **Logic Features**
 - **Page features:**
 - » **Flags**
 - » **Repeats**
 - » **Follow Ons**
 - » **Skip If**
 - **Special References**

Custom Expressions

- **Evaluated by Javascript**
 - See [documentation](#) for more details
- **Examples in TabSINT documentation**

Meaning	Code
If the previous question was correct	<code>result.correct</code>
If the previous result was incorrect	<code>!result.correct</code>
If the previous response was "dog"	<code>result.response === 'dog'</code>
If the previous response was 34 and the <code>usesHearingProtection</code> flag is set.	<code>(result.response === '34') && flags.usesHearingProtection</code>
If the subject chose both earPlugs and other:	<code>arrayContains(result.response, 'earPlugs') && arrayContains(result.response, 'other')</code>

Page Features

- **setFlag**
 - set at the end of any page and then use in custom expression
- **repeatPage**
 - repeat the same page based on conditional expression
- **followOns**
 - ask one (or more) immediate follow-up questions if response meets some criteria
- **skipIf**
 - skip any page based on response

Special References

- **@PARTIAL**
 - Specify a final subprotocol to run before ending when terminated via 'End Exam and Submit Partial Results'
 - » Used in protocolId field
- **@END_ALL**
 - Automatically end the test no matter where in the protocol
 - » Used in reference field

```
{
  "protocolId": "@PARTIAL",
  "pages": [
    {
      "id": "partial",
      "questionMainText": "@PARTIAL Reference",
      "instructionText": "Shown when exam is ended early"
    }
  ]
},
```

```
{
  "conditional": "result.response == 'B'",
  "target": {
    "reference": "@END_ALL"
  }
},
```

Links

- [Documentation](#)
- [**Workshop example**](#)
- [**Additional examples**](#)

Future Workshops

Session 5 will be a Q&A session in early May.

Please email any questions you have or topics you want discussed to tmr@create.com